



#### ARSET

Applied Remote Sensing Training http://arset.gsfc.nasa.gov



@NASAARSET

# NASA Trace Gas Products for Air Quality Applications

Pawan Gupta & ARSET Team

Satellite Remote Sensing of Air Quality: Data, Tools, and Applications

Tuesday, May 23, 2017 – Friday, May 26, 2017 Indian Institute of Tropical Meteorology, Pune, India

# Satellite Remote Sensing of Trace Gases for Air Quality in a Nutshell

### Surface Monitoring

- Compared to aerosol instrumentation, satellite trace gas instrumentation is generally **not as sensitive** to surface pollution
- -Exceptions: nitrogen dioxide and sulfur dioxide

### Emissions Inventories and Modeling

 Trace gas observations from space have been useful for constraining emissions inventories

### Vertical Profile Information in the Free Troposphere

 Also available for some products (e.g. CO) and derived using the pressure dependence of spectral bands

# Satellite Remote Sensing of Trace Gases for Air Quality in a Nutshell

### Nitrogen Dioxide

- Good sensitivity in the planetary boundary layer (PBL)
- -Fire smoke, industrial and transportation sources, stationary sources, top-down emissions inventories

### Sulfur Dioxide, Ozone, and Formaldehyde


- -Limited sensitivity in the PBL
- Sensitive to large point sources, such as electrical generating units and volcanoes

# Satellite Remote Sensing of Trace Gases for Air Quality in a Nutshell


- Carbon Monoxide
  - –Good mid-tropospheric sensitivity
  - Useful for monitoring long-range transport of smoke
- Carbon Dioxide and Methane
  - -Low spatial resolution
  - -Captures global trends

### Measuring Trace Gases from Space

- Detect backscattered and/or emitted thermal radiation
- We know the distinct absorption spectra of each trace gas
- We can identify a "fingerprint" for each atmospheric constituent
- Retrieval algorithms (a model) infer physical quantities such as number density, partial pressure, and column amount




### How Satellites Measure Trace Gases




- Trace gases use the signature of gas absorption
- All satellite remote sensing measurements of the troposphere are based on the use of electromagnetic radiation and its interaction with constituents in the atmosphere

# Satellite Measurements Take Advantage of Distinct Absorption Spectra




## Vertical Distribution of O<sub>3</sub>, SO<sub>2</sub>, and NO<sub>2</sub>

- Very little information can be obtained on the vertical distribution of trace gases
- Measurements at different wavelengths (technique of combining UV, visible, and IR measurements) provide some vertical information
  - –penetration depth of photons increases with increasing wavelengths
  - –Example: volcanic plumesof SO<sub>2</sub>



# Hyperspectral Instruments Satellite UV-Visible Spectrometers

Instrument	Satellite	Wavelength
GOME	ERS-2	240 – 800 nm
SCIAMACHY	Envisat	240 – 1750 nm
OMI	EOS-Aura	270 – 500 nm
GOME-2	Metop-A	240 – 800 nm



### Data Formats & Resolutions

Data Level	Description
Level 0	Raw data at full instrument resolution
Level 1A	Raw data, including radiometric and geometric calibration coefficients and geo-referencing parameters (e.g. platform ephemeris) computed and appended, but not applied to Level 0 data
Level 1B	Level 1A data that has been processed to sensor units (not all instruments have Level 1B source data)
Level 2	Derived geophysical variables at the same resolution and location as Level 1 source data
Level 2G & 3	Variables mapped on uniform space-time grid scales, usually with some completeness and consistency
Level 4	Model output or results from analyses of lower level data (e.g. variables derived from multiple measurements)

### **Spatial Resolution: Trace Gases**


- Spatial resolution of current satellite instruments (10s of km diameter)
  - good enough to map tropospheric concentration fields on local to regional scales
  - -fine enough to resolve individual power plants and large cities
- For species with short atmospheric lifetimes (e.g. NO<sub>2</sub>), averaging over larger satellite pixels can lead to significant dilution of signals from point sources, complicating quantitative analysis and separation of emission sources
- For quantitative analysis: Level 2 and high resolution gridded Level 3 data are optimal

Source: Richter, 2010

## Advantages of Using Level 3 vs. Level 2 Data

- Uniform grid
- One file per day
- Smaller sized files
- Quality flags and filtering criteria have been applied

### Perspective...



### Quantification of Gas Abundances

Satellite Tracer	Units
OMI O <sub>3</sub> , SO <sub>2</sub>	Dobson Units
OMI NO <sub>2</sub> , Column Amounts (also AIRS and MOPITT CO)	Molecules/cm <sup>2</sup>
AIRS and MOPITT CO Vertical Levels	Volume Mixing Ratio


### Ozone Measuring Instrument (OMI)


- Launched July 15, 2004
- NASA EOS Aura Satellite
- Nadir-viewing UV/Visible
  - -270 310 nm at 0.6 nm
  - -310 500 nm at 0.45 nm
- 1:40 p.m. equatorial crossing time
- 13x24 km<sup>2</sup> at nadir
- Daily global coverage

- Products
  - -Total Column O<sub>3</sub>
  - -Tropospheric Column O<sub>3</sub> (experimental but not applicable in the midlatitudes)
  - Aerosol optical depth (in UV)
  - -Column Formaldehyde
  - -Column NO<sub>2</sub>
  - -Column SO<sub>2</sub>

#### **Data Granule**


- Product File
  - –covers sunlit portion of the orbit with an approx. 2,600 km wide swath
  - -contains 60 binned pixels or scenes per viewing line
- 14 or 15 granules are produced daily, providing fully contiguous coverage of the globe






### Important Information Regarding OMI

- Almost 50% data loss since 2008 (row anomaly effect)
- Affects O<sub>3</sub>, SO<sub>2</sub>, and to some extent NO<sub>2</sub> OMI products








### OMI Ozone in the Troposphere

- OMI is not sensitive to ozone near the surface
- There are tropospheric ozone products in development
  - -they currently cannot be used for air quality monitoring
- Retrieval of boundary layer O<sub>3</sub> from satellite remote sensing remains a daunting task

## OMI Formaldehyde (CH<sub>2</sub>O)

- Data is reliable for 2004-2009 only
- Data re-processing is planned to account for the growing background noise and row anomalies

HCHO is a proxy for isoprene emissions




Source: Martin, Randall. Satellite remote sensing of surface air quality. Atmospheric Environment 42(34), 7823-7843, 2008.



### OMI SO<sub>2</sub> in the Boundary Layer

- Dataset Short Name = OMSO2e
  - -Product Level: 3
  - -Begin: October 1, 2004
  - Resolution: 0.25° lon x0.25°lat
- Cloud-screened best measurement
  - -Frequency: daily
  - -Granule (File) Coverage:15 orbits
  - -File Size (approx): 5 mb




- Contains best pixel data, screened for OMI row anomaly, clouds, and other data quality flags
- Data: <a href="http://disc.sci.gsfc.">http://disc.sci.gsfc.</a>

   nasa.gov/Aura/data holdings/OMI/omso2e\_v00
   3.shtml


### Perspective: What is Considered High SO<sub>2</sub>?


## 2005-2010 Mean SO<sub>2</sub> Over Canadian Oil Sands



McLinden, C. A., et al. (2012), Air quality over the Canadian oil sands: A first assessment using satellite observations, Geophys. Res. Lett., 39, L04804, doi:10.1029/2011GL050273.


## OMI SO<sub>2</sub> from Kasatochi Volcano August 8-12, 2008






## Perspective: What is considered high SO<sub>2</sub>?

## U.S. Source #1: Bowen Coal Power Plant, Georgia (3500 MW), SO<sub>2</sub> Emissions: 170 kT in 2006









"In **2008**, the mammoth construction program yielded the first scrubbers, sophisticated equipment that will reduce our overall systems emissions by as much as 90 percent"

#### Georgia Power website

Source: V. Fioletov, et al., 2011


## OMI NO<sub>2</sub>






## Nitrogen Dioxide (NO<sub>2</sub>)

- NO<sub>2</sub> is produced when coal and gasoline are burned
  - -comes out of tailpipes and smokestacks
- Unhealthy to breathe and correlated with morbidity and mortality
  - likely since it is emitted alongside air toxins & is a necessary ingredient for ozone formation



Source: Duncan, B.N. et al. (2016)

# OMI Detects NO<sub>2</sub> Increases from ONG Activities 2005-2014



North Dakota




**Suomi NPP VIIRS Lights at Night** 

Texas




National Aeronautics and Space Administration


### Satellite and AQS NO2 Trends



## Estimating Satellite Based Surface NO<sub>2</sub>




Scattering by Earth surface and atmosphere



$$\mathbf{S}_{\mathrm{O}} = \mathbf{\Omega}_{\mathrm{O}} \left[ \frac{\mathbf{S}_{\mathrm{M}}}{\mathbf{\Omega}_{\mathrm{M}}} \right]$$


#### **Model Profile**



**S** → Surface Concentration

 $\Omega \rightarrow$  Tropospheric column

## Ground-Level Afternoon NO<sub>2</sub> Inferred from OMI for 2005



- Also available at: <a href="http://fizz.phys.dal.ca/~atmos/">http://fizz.phys.dal.ca/~atmos/</a>
- Note: this is a research product and not an official NASA product

Source: Lok Lamsal




### Carbon Monoxide

- Top Column Density
- Also sensitive to vertical distribution of CO
- Greatest sensitivity to CO variability is at 500 mb




 Mixing ratio can be larger away from the source




### **Current CO Sensors**


## AIRS: Atmospheric Infrared Sounder



## MOPITT: Measurements of Pollution in The Troposphere




IASI: Infrared Atmospheric Sounding Interferometer



### Atmospheric Infrared Sounder (AIRS)

### http://airs.jpl.nasa.gov/


- Operational since Sep 2002
- Nadir sounding instrument
- Pixel size
  - -14 km at nadir
  - -41x21 km edges
- Swath Width: 1,650 km
- Equator Crossing Times
  - -1:30 (ascending)
  - -13:30 (descending)
- Column Measurements in molecules/cm<sup>3</sup>



- Profile Measurements:
  - -9 vertical layers
  - -901.866 hPa 0.16 hPa
- Data source: Level 2 pixel and Level 3 gridded
   1° x1° resolution

### **AIRS**

- Has excellent global coverage with 'minor' gaps – particularly over CONUS
- Can easily track biomass burning plumes
  - –AIRS swath width is~1650 km where MOPITT is640 km
  - Twice daily coverage with AIRS (daytime and nighttime)
- Ascending Orbit = Daytime
- Descending Orbit = Nighttime




### AIRS vs. MOPPITT CO


#### **AIRS Level 2 from NRT Website**




## AIRS Level 3, 1° x1° from



MOPPITT Level 3, 1° x1°



## Long Range Transport of CO





## OMI SO<sub>2</sub> Gridded Product Summary

SO <sub>2</sub> Product	Level	Data Short Name	Sensitivity	Use
PBL SO <sup>2</sup>	L3 0.25° x0.2 5°	OMSO2e	0.6 km	Fossil fuel, industry
TRL SO <sup>2</sup>	L2G 0.25° x0.2 5°	OMSO2G	3 km	Industry outflow
TRM SO <sup>2</sup>	L2G 0.25° x0.2 5°	OMSO2G	5 km	Optimized for volcanic degassing
CayeatoUnl screened fo	L2G ikeչthe <sub>x</sub> QMS r <sub>5</sub> clouds, sz	SORSÓÞest a, quality fl	, prթվաct, ags, and ro	LEXO OSANO PROPERTO LE VINTO PROPINS DE LA P

## Level 2 Pixel (Footprint) Size at Nadir

NASA	AIRS	14 x 14 km		
NASA	MOPITT	22 x 22km		
NASA	TES	■ 8.3 km 5.3 km		
esa	SCIAMACHY	30 km 60 km		
esa	IASI	12 x 12 km		

	MOPITT	AIRS	TES	IASI	SCIAMACY
Product / Pixel size	22 x 22 km	14 x 14 km	5.3 x 8.3 km 100 m between pixels	50 km 12 x 12 km	30 x 60 km
Swath Width	650 km	1,650 km	N/A	2,200 km	1,000 km
Global Coverage / Repeat Cycle	3 day composite for global coverage	2x per day (day & night)	16 day repeat cycle	2x per day (day & night)	6 days
Overpass Time	10:30	13:30	2:30, 14:30	9:30, 21:30	10:00

	MOPITT	AIRS	TES	IASI	SCIAMACY
Product Resolution	L3 1° Grid	L3 1° Grid	L3 5 x 8 km	NO L3 Product	L3 0.5° Grid
Products Available	L2 L3, Daily, Monthly	L2 granule L3	L2 granule	L2 NOAA & ESA	2B-swath 3-global
Vertical Sensitivity	mid & lower troposphere	mid tropo- sphere	mid & lower troposphere	mid tropo- sphere	total column only
Product Accuracy	TIR: 10% Near Surface: 30%	10-20%	20%	<10%	10-20%

	MOPITT	AIRS	TES	IASI	SCIAMACY
Notes	• TIR and NIR channels	<ul> <li>QA flags in L2 and L3</li> <li>Next product will include near surface</li> </ul>	<ul> <li>Report data for clouds</li> <li>0-25%</li> <li>Simultaneous trace gas</li> </ul>	<ul> <li>250</li> <li>km</li> <li>sampli</li> <li>ng</li> <li>ESA</li> <li>Should</li> <li>averag</li> <li>e to 4 x</li> <li>5°</li> </ul>	

	MOPITT	AIRS	TES	IASI	SCIAMACHY
Product/pixel size	22 x 22 Km	14 x 14 km	5.3 x 8.3 KM 100 M between pixels	50 KM 12 x 12 KM	30 x 60KM
Swath width	650 KM	1650 KM	N/A	2200 KM	1000 KM
Global Coverage/ Repeat Cycle	3 Days Composite for global coverage	2X per day (day and night)	16 days Repeat Cycle	2X per day (day and night)	6 Days
Overpass time	10:30 AM	13:30	2:30 AM / PM	9:30 AM/PM	10:00 AM
Product Resolution	L3 1 Degree grid	L3 1 Degree grid	L3 5x8km	NO L3 Product	L3 0.5 Degree grid
Products available	L2 L3 Daily, Monthly	Level 2 (granule) Level 3	L2 granule	L2 NOAA and ESA	2B - swath 3 - global
Vertical sensitivity	Mid and lower troposphere	Mid- Troposphere	mid and lower troposphere	mid troposphere	Total column only
Product accuracy	TIR - 10% Near Surface 30%	10 - 20%	20%	< 10%	10 - 20%
Other notes	TIR and NIR Channels	QA flags in L2 and L3	Report data for clouds 0 -25% Simultaneous trace gas	250 KM sampling ESA Should avg. to 4x5 deg.	